



Bearing No. 6804ZZ

D	32 mm
d	20 mm
B	7 mm
C	7 mm
rn	0,3 mm
Bore	0.787 Inch 20 Millimeter
Noun	Bearing
da max	22,5 mm
UNSPSC	31171504
Weight	0,019 Kg
r min.	0,3 mm
ra max.	0,3 mm
da min.	22 mm
Da max.	30 mm
Category	Single Row Ball Bearing
Size (mm)	20x32x7
Snap Ring	No
Inventory	0.0
Enclosure	2 Metal Shields
Width (mm)	7
bore type:	Round
Weight / LBS	0.042
Inch - Metric	Metric
closure type:	Double Shielded
Product Group	B00308
Cage Material	Steel
bore diameter:	20 mm
Keyword String	Ball
overall width:	7 mm

cage material:	Steel
fillet radius:	0.3 mm
Other Features	Deep Groove Shell Alvania Prelubricated
Bearing number	6804ZZ
Precision Class	ABEC 1 ISO P0
Rolling Element	Ball Bearing
finish/coating:	Uncoated
Long Description	20MM Bore; 32MM Outside Diameter; 7MM Outer Race Width; 2 Metal Shields; Ball Bearing; ABEC 1 ISO P0; No Filling Slot; No Snap Ring; No Internal Special Features; C0-Medium Internal Clearance; Steel
Manufacturer URL	http://www.ntnamerica.com
Inner Race Width	0 Inch 0 Millimeter
Outside Diameter	1.26 Inch 32 Millimeter
Outer Race Width	0.276 Inch 7 Millimeter
precision rating:	ISO Class 0
outer ring width:	7 mm
inner ring width:	7 mm
Weight / Kilogram	0
bearing material:	High Carbon Chrome Steel
Manufacturer Name	NTN
outside diameter:	32 mm
Bore Diameter (mm)	20
Internal Clearance	C0-Medium
snap ring included:	Without Snap Ring
Outer Diameter (mm)	32
internal clearance:	CN

Minimum Buy Quantity	N/A
static load capacity:	2470 N
row type & fill slot:	Single Row Non-Fill Slot
maximum rpm (grease):	21000 rpm
Harmonized Tariff Code	8482.10.50.68
dynamic load capacity:	4000 N
Internal Special Features	No
(Grease) Lubrication Speed	21 000 r/min
manufacturer product page:	Click here
operating temperature range:	-40 to 120 °C
Basic static load rating (C0)	2,47 kN
Basic dynamic load rating (C)	4 kN
Maximum Capacity / Filling Slot	No