



Bearing No. 6804ZZNR

D	32,000 mm
C	7,000 mm
B	7,000 mm
d	20,000 mm
Bore	0.787 Inch 20 Millimeter
Noun	Bearing
UNSPSC	31171504
series:	68
Category	Single Row Ball Bearing
Size (mm)	20x32x7
Enclosure	2 Metal Shields
Snap Ring	Yes
Inventory	0.0
Width (mm)	7,000
bore type:	Round
maximum rpm:	21000 RPM
Weight / LBS	0.044
Cage Material	Steel
closure type:	Double Shielded
Product Group	B00308
Inch - Metric	Metric
Bearing number	6804ZZNR
bore diameter:	20 mm
overall width:	7 mm
fillet radius:	0.3 mm
cage material:	Steel
Keyword String	Ball
Rolling Element	Ball Bearing
finish/coating:	Uncoated

Precision Class	ABEC 1 ISO P0
Manufacturer URL	http://www.ntnamerica.com
Outside Diameter	1.26 Inch 32 Millimeter
Long Description	20MM Bore; 32MM Outside Diameter; 7MM Outer Race Diameter; 2 Metal Shields; Ball Bearing; ABEC 1 ISO P0; No Filling Slot; Yes Snap Ring; No Internal Special Features
Outer Race Width	0.276 Inch 7 Millimeter
Weight / Kilogram	0.02
outer ring width:	7 mm
inner ring width:	7 mm
bearing material:	High Carbon Chrome Steel
Manufacturer Name	NTN
outside diameter:	32 mm
precision rating:	ISO Class 0
Bore Diameter (mm)	20,000
Internal Clearance	C0-Medium
Outer Diameter (mm)	32,000
snap ring included:	With Snap Ring
internal clearance:	CN
Minimum Buy Quantity	N/A
row type & fill slot:	Single Row Non-Fill Slot
static load capacity:	2470 N
maximum rpm (grease):	21000 rpm
dynamic load capacity:	4000 N
Harmonized Tariff Code	8482.10.50.68
Manufacturer Item Number	6804JRZZNR/2AS
Internal Special Features	No

manufacturer product page:	Click here
operating temperature range:	-40 to 120 °C
Maximum Capacity / Filling Slot	No