



Bearing No. 6413

D	160 mm
d	65 mm
B	37 mm
C	37 mm
f0	12.4
Cu	6.20
Cr	148
C0r	79.2
Bore	2.559 Inch 65 Millimeter
Noun	Bearing
UNSPSC	31171504
Weight	3,3 Kg
r(min)	2.1
r min.	2,1 mm
da min.	76 mm
ra(max)	2
Da max.	149 mm
Da(max)	149
da(min)	76
ra max.	2 mm
Category	Single Row Ball Bearing
Oil lub.	5200
Inventory	0.0
Enclosure	Open
Size (mm)	65x160x37
Snap Ring	No
Width (mm)	37
Grease lub.	4300
Bearing No.	6413

Weight / LBS	7.868
Product Group	B00308
Cage Material	Steel
Inch - Metric	Metric
Keyword String	Ball
Bearing number	6413
Precision Class	ABEC 1 ISO P0
Rolling Element	Ball Bearing
Outside Diameter	6.299 Inch 160 Millimeter
Long Description	65MM Bore; 160MM Outside Diameter; 37MM Outer Race Diameter; Open; Ball Bearing; ABEC 1 ISO P0; No Filling Slot; No Snap Ring; No Internal Special Features
Outer Race Width	1.457 Inch 37 Millimeter
(Refer.)Mass(kg)	3.30
Manufacturer URL	http://www.koyousa.com
Weight / Kilogram	3.572
Manufacturer Name	KOYO
Internal Clearance	C0-Medium
Bore Diameter (mm)	65
Outer Diameter (mm)	160
Minimum Buy Quantity	N/A
Harmonized Tariff Code	8482.10.50.68
(Oil) Lubrication Speed	5200 r/min
Manufacturer Item Number	6413
Internal Special Features	No
(Grease) Lubrication Speed	4300 r/min

Basic static load rating (C0)	79,2 kN
Basic dynamic load rating (C)	118 kN
Maximum Capacity / Filling Slot	No