



Bearing No. 6803ZZE

D	26 mm
d	17 mm
B	5 mm
C	5 mm
Noun	Bearing
Bore	0.669 Inch 17 Millimeter
Width	5 mm
UNSPSC	31171504
r min.	0.3 mm
Weight	0.008 Kg
da min.	19 mm
Da max.	24 mm
ra max.	0.3 mm
Category	Single Row Ball Bearing
ra (max)	0.3 mm
da (min)	19 mm
Da (max)	24 mm
Factor fo	16.1
Inventory	0.0
Bore Size	17 mm
Bore Type	Cylindrical Bore
Enclosure	2 Metal Shields
Snap Ring	No
Size (mm)	17x26x5
Width (mm)	5
Weight / LBS	0.02
Configuration	Single Row
Product Group	B00308
Inch - Metric	Metric

Keyword String	Ball
Bearing number	6803ZZE
Rolling Element	Ball Bearing
Precision Class	ABEC 1 ISO P0
Long Description	17MM Bore; 26MM Outside Diameter; 5MM Outer Race Diameter; 2 Metal Shields; Ball Bearing; ABEC 1 ISO P0; No Filling Slot; No Snap Ring; No Internal Special Features
Manufacturer URL	http://www.nachi.com
Outer Race Width	0.197 Inch 5 Millimeter
Outside Diameter	1.024 Inch 26 Millimeter
Radial Clearance	0.003 to 0.018 mm
Weight / Kilogram	0.009
Manufacturer Name	NACHI
Internal Clearance	C0-Medium
Bore Diameter (mm)	17
Static Load Rating	1,570 N
Dynamic Load Rating	2,630 N
Outer Diameter (mm)	26
Minimum Buy Quantity	N/A
Fillet Radius/Chamfer	0.3 mm
Harmonized Tariff Code	8482.10.50.68
Limiting Speed - Grease	26,000 rpm
Manufacturer Item Number	6803 ZZE BS2S
Internal Special Features	No
Basic static load rating (C0)	1,57 kN
Basic dynamic load rating (C)	2,63 kN

Maximum Capacity / Filling Slot	No
------------------------------------	----