



### Bearing No. 6804

D	32 mm
d	20 mm
B	7 mm
C	7 mm
f0	15.5
Cu	0.100
Cr	5.00
C0r	2.45
Bore	0.787 Inch   20 Millimeter
Noun	Bearing
UNSPSC	31171504
Weight	0,018 Kg
r(min)	0.3
r min.	0,3 mm
da min.	22 mm
ra(max)	0.3
Da max.	30 mm
Da(max)	30
da(min)	22
ra max.	0,3 mm
Category	Single Row Ball Bearing
Oil lub.	25000
Inventory	0.0
Enclosure	Open
Size (mm)	20x32x7
Snap Ring	No
Width (mm)	7
Grease lub.	21000
Bearing No.	6804

Weight / LBS	0.043
Product Group	B00308
Cage Material	Steel
Inch - Metric	Metric
Keyword String	Ball
Bearing number	6804
Precision Class	ABEC 1   ISO P0
Rolling Element	Ball Bearing
Outer Race Width	0.276 Inch   7 Millimeter
Long Description	20MM Bore; 32MM Outside Diameter; 7MM Outer Race Diameter; Open; Ball Bearing; ABEC 1   ISO P0; No Filling Slot; No Snap Ring; No Internal Special Features
Outside Diameter	1.26 Inch   32 Millimeter
(Refer.)Mass(kg)	0.018
Manufacturer URL	<a href="http://www.koyousa.com">http://www.koyousa.com</a>
Weight / Kilogram	0.019
Manufacturer Name	KOYO
Internal Clearance	C0-Medium
Bore Diameter (mm)	20
Outer Diameter (mm)	32
Minimum Buy Quantity	N/A
Harmonized Tariff Code	8482.10.50.68
(Oil) Lubrication Speed	25000 r/min
Manufacturer Item Number	6804
Internal Special Features	No
(Grease) Lubrication Speed	21000 r/min
Basic static load rating (C0)	2,45 kN

Basic dynamic load rating (C)	4 kN
Maximum Capacity / Filling Slot	No