



### Bearing No. 6804LLU

C	7 mm
d	20 mm
B	7 mm
D	32 mm
Bore	0.787 Inch   20 Millimeter
Noun	Bearing
da max	22,5 mm
UNSPSC	31171504
Weight	0,019 Kg
r min.	0,3 mm
da min.	22 mm
Da max.	30 mm
ra max.	0,3 mm
series:	68
Category	Single Row Ball Bearing
Enclosure	2 Seals
Snap Ring	No
Size (mm)	20x32x7
Inventory	0.0
bore type:	Round
Width (mm)	7
maximum rpm:	13000 RPM
Weight / LBS	0.038
Inch - Metric	Metric
Product Group	B00308
closure type:	Double Sealed
Cage Material	Steel
Other Features	Deep Groove   Double Lip Friction Nitrile Rubber Seal   -20 To

	120 Deg C   Shell Alvania Prelubricated
Keyword String	Ball
Bearing number	6804LLU
cage material:	Steel
Enclosure Type	Contact Seal
bore diameter:	20 mm
overall width:	7 mm
fillet radius:	0.3 mm
Rolling Element	Ball Bearing
finish/coating:	Uncoated
Precision Class	ABEC 1   ISO P0
Reference speed	13 000 r/min
Inner Race Width	0 Inch   0 Millimeter
Outer Race Width	0.276 Inch   7 Millimeter
Long Description	20MM Bore; 32MM Outside Diameter; 7MM Outer Race Diameter; 2 Seals; Ball Bearing; ABEC 1   ISO P0; No Filling Slot; No Snap Ring; No Internal Special Features
Outside Diameter	1.26 Inch   32 Millimeter
Manufacturer URL	<a href="http://www.ntnamerica.com">http://www.ntnamerica.com</a>
inner ring width:	7 mm
precision rating:	ISO Class 0
outside diameter:	32 mm
Weight / Kilogram	0.017
bearing material:	High Carbon Chrome Steel
Manufacturer Name	NTN
outer ring width:	7 mm
Bore Diameter (mm)	20

Internal Clearance	C0-Medium
internal clearance:	CN
snap ring included:	Without Snap Ring
Outer Diameter (mm)	32
Minimum Buy Quantity	N/A
row type & fill slot:	Single Row Non-Fill Slot
static load capacity:	2470 N
maximum rpm (grease):	13000 rpm
Harmonized Tariff Code	8482.10.50.68
dynamic load capacity:	4000 N
Manufacturer Item Number	6804JRLLU/2AS
Internal Special Features	No
manufacturer product page:	<a href="#">Click here</a>
operating temperature range:	-40 to 120 °C
Basic dynamic load rating (C)	4 kN
Basic static load rating (C0)	2,47 kN
Maximum Capacity / Filling Slot	No