



Bearing No. 6803LLU

D	26 mm
d	17 mm
B	5 mm
C	5 mm
Bore	0.669 Inch 17 Millimeter
Noun	Bearing
da max	19,5 mm
UNSPSC	31171504
Weight	0,008 Kg
r min.	0,3 mm
Da max.	24 mm
ra max.	0,3 mm
series:	68
da min.	19 mm
Category	Single Row Ball Bearing
Inventory	0.0
Enclosure	2 Seals
Snap Ring	No
Size (mm)	17x26x5
Width (mm)	5
bore type:	Round
maximum rpm:	15000 RPM
Weight / LBS	0.018
Inch - Metric	Metric
Cage Material	Steel
closure type:	Double Sealed
Product Group	B00308
Keyword String	Ball
Other Features	Deep Groove Double Lip Friction Nitrile

	Rubber Seal -20 To 120 Deg C Shell Alvania Prelubricated
Enclosure Type	Contact Seal
Bearing number	6803LLU
bore diameter:	17 mm
overall width:	5 mm
fillet radius:	0.3 mm
cage material:	Steel
Rolling Element	Ball Bearing
finish/coating:	Uncoated
Precision Class	ABEC 1 ISO P0
Reference speed	15 000 r/min
Outside Diameter	1.024 Inch 26 Millimeter
Outer Race Width	0.197 Inch 5 Millimeter
Long Description	17MM Bore; 26MM Outside Diameter; 5MM Outer Race Width; 2 Seals; Ball Bearing; ABEC 1 ISO P0; No Filling Slot; No Snap Ring; No Internal Special Features; C0-Medium Internal Clearance; Steel Cage; C
Inner Race Width	0 Inch 0 Millimeter
Manufacturer URL	http://www.ntnamerica.com
Weight / Kilogram	0
outer ring width:	5 mm
Manufacturer Name	NTN
bearing material:	High Carbon Chrome Steel
inner ring width:	5 mm
precision rating:	ISO Class 0

outside diameter:	26 mm
Internal Clearance	C0-Medium
Bore Diameter (mm)	17
snap ring included:	Without Snap Ring
Outer Diameter (mm)	26
internal clearance:	CN
Minimum Buy Quantity	N/A
static load capacity:	1460 N
row type & fill slot:	Single Row Non-Fill Slot
maximum rpm (grease):	15000 rpm
Harmonized Tariff Code	8482.10.50.68
dynamic load capacity:	2230 N
Internal Special Features	No
manufacturer product page:	Click here
operating temperature range:	-40 to 120 °C
Basic dynamic load rating (C)	2,23 kN
Basic static load rating (C0)	1,46 kN
Maximum Capacity / Filling Slot	No