



## Bearing No. 6803VV

D	26 mm
d	17 mm
B	5 mm
C	5 mm
r	0.3
C0	1.57
fo	15.7
ra	0.3
D_	26
B_	5
Z_	13
DI_	18.722
D_a	24
DE_	24.278
SRI	1.44
DA_	2.778
SRE	1.44
Noun	Bearing
SREN	-0.01
SDM_	21.5
SRIN	-0.01
yobi	6803VV
Bore	0.669 Inch   17 Millimeter
mass	0.007
bomp	0
SREX	0.01
SBRG	18
SRIX	0.01
KBRG	6151

UNSPSC	31171504
ALPHA_	0
LangID	1
r min.	0,3 mm
da max	19 mm
da min	19
Weight	0,007 Kg
C_conv	2630
GRS rpm	26000
hidYobi	6803VV
da min.	19 mm
Da max.	24 mm
ra max.	0,3 mm
hidTable	ecat_NSRDGB
Category	Single Row Ball Bearing
Inventory	0.0
Snap Ring	No
Size (mm)	17x26x5
Enclosure	2 Seals
Prod_Type3	DGBB_SR_VV
bore type:	Round
Width (mm)	5
Weight / LBS	0.008
Cage Material	Steel
Product Group	B00308
closure type:	Two Non-Contact Seals
Inch - Metric	Metric
Bearing number	6803VV
bore diameter:	17 mm
overall width:	5 mm
Keyword String	Ball
Enclosure Type	Non-Contact Seal

Rolling Element	Ball Bearing
Precision Class	ABEC 1   ISO P0
Outside Diameter	1.024 Inch   26 Millimeter
Long Description	17MM Bore; 26MM Outside Diameter; 5MM Outer Race Diameter; 2 Seals; Ball Bearing; ABEC 1   ISO P0; No Filling Slot; No Snap Ring; No Internal Special Features
Outer Race Width	0.197 Inch   5 Millimeter
Manufacturer URL	<a href="http://www.nskamericas.com">http://www.nskamericas.com</a>
Weight / Kilogram	0.008
bearing material:	Steel
outside diameter:	26 mm
Manufacturer Name	NSK
maximum rpm (oil):	30000 rpm
Bore Diameter (mm)	17
Internal Clearance	C0-Medium
Outer Diameter (mm)	26
snap ring included:	Without Snap Ring
internal clearance:	C0
Minimum Buy Quantity	N/A
maximum rpm (grease):	26000 rpm
static load capacity:	355 lbs
row type & fill slot:	Single Row Non-Fill Slot
manufacturer catalog:	<a href="#">Click here</a>
dynamic load capacity:	590 lbs
Harmonized Tariff Code	8482.10.50.68
manufacturer upc number:	029176029783
Manufacturer Item Number	6803VV

Internal Special Features	No
(Grease) Lubrication Speed	26 000 r/min
Basic static load rating (C0)	1,57 kN
Basic dynamic load rating (C)	2,63 kN
Maximum Capacity / Filling Slot	No