



Bearing No. 6803ZZ

C	5 mm
d	17 mm
D	26 mm
B	5 mm
Bore	0.669 Inch 17 Millimeter
Noun	Bearing
Weight	0,008 Kg
r min.	0,3 mm
da max	19,5 mm
UNSPSC	31171504
da min.	19 mm
Da max.	24 mm
ra max.	0,3 mm
Category	Single Row Ball Bearing
Snap Ring	No
Enclosure	2 Metal Shields
Inventory	0.0
Size (mm)	17x26x5
Width (mm)	5
bore type:	Round
Weight / LBS	0.017
Product Group	B00308
Inch - Metric	Metric
closure type:	Double Shielded
Cage Material	Steel
bore diameter:	17 mm
overall width:	5 mm
Keyword String	Ball
cage material:	Steel

fillet radius:	0.3 mm
Bearing number	6803ZZ
Precision Class	ABEC 1 ISO P0
Rolling Element	Ball Bearing
finish/coating:	Uncoated
Long Description	17MM Bore; 26MM Outside Diameter; 5MM Outer Race Diameter; 2 Metal Shields; Ball Bearing; ABEC 1 ISO P0; No Filling Slot; No Snap Ring; No Internal Special Features
Manufacturer URL	http://www.ntnamerica.com
Outer Race Width	0.197 Inch 5 Millimeter
Outside Diameter	1.024 Inch 26 Millimeter
precision rating:	ISO Class 0
outside diameter:	26 mm
outer ring width:	5 mm
inner ring width:	5 mm
Weight / Kilogram	0.008
bearing material:	High Carbon Chrome Steel
Manufacturer Name	NTN
Bore Diameter (mm)	17
Internal Clearance	C0-Medium
Outer Diameter (mm)	26
internal clearance:	CN
snap ring included:	Without Snap Ring
Minimum Buy Quantity	N/A
static load capacity:	1460 N
row type & fill slot:	Single Row Non-Fill Slot
maximum rpm (grease):	24000 rpm

dynamic load capacity:	2230 N
Harmonized Tariff Code	8482.10.50.68
Manufacturer Item Number	6803ZZ/5K
Internal Special Features	No
(Grease) Lubrication Speed	24 000 r/min
manufacturer product page:	Click here
operating temperature range:	-40 to 120 °C
Basic dynamic load rating (C)	2,23 kN
Basic static load rating (C0)	1,46 kN
Maximum Capacity / Filling Slot	No