



Bearing No. 6802

D	24 mm
d	15 mm
B	5 mm
C	5 mm
f0	15.8
Cu	0.050
Cr	2.60
C0r	1.25
Bore	0.591 Inch 15 Millimeter
Noun	Bearing
UNSPSC	31171504
Weight	0,007 Kg
r(min)	0.3
r min.	0,3 mm
da min.	17 mm
ra(max)	0.3
Da max.	22 mm
Da(max)	22
da(min)	17
ra max.	0,3 mm
Category	Single Row Ball Bearing
Oil lub.	33000
Inventory	0.0
Enclosure	Open
Size (mm)	15x24x5
Snap Ring	No
Width (mm)	5
Grease lub.	28000
Bearing No.	6802

Weight / LBS	0.017
Product Group	B00308
Cage Material	Steel
Inch - Metric	Metric
Keyword String	Ball
Bearing number	6802
Precision Class	ABEC 1 ISO P0
Rolling Element	Ball Bearing
Outer Race Width	0.197 Inch 5 Millimeter
Long Description	15MM Bore; 24MM Outside Diameter; 5MM Outer Race Diameter; Open; Ball Bearing; ABEC 1 ISO P0; No Filling Slot; No Snap Ring; No Internal Special Features
Outside Diameter	0.945 Inch 24 Millimeter
(Refer.)Mass(kg)	0.007
Manufacturer URL	http://www.koyousa.com
Weight / Kilogram	0.008
Manufacturer Name	KOYO
Internal Clearance	C0-Medium
Bore Diameter (mm)	15
Outer Diameter (mm)	24
Minimum Buy Quantity	N/A
Harmonized Tariff Code	8482.10.50.68
(Oil) Lubrication Speed	33000 r/min
Manufacturer Item Number	6802
Internal Special Features	No
(Grease) Lubrication Speed	28000 r/min
Basic static load rating	1,25 kN

(C0)	
Basic dynamic load rating (C)	2,1 kN
Maximum Capacity / Filling Slot	No