



## Bearing No. 6802

D	24 mm
d	15 mm
B	5 mm
C	5 mm
r	0.3
Z_	14
C0	1.26
ra	0.3
fo	15.8
D_	24
B_	5
DI_	17.119
SRI	1.23
DE_	21.881
DA_	2.381
SRE	1.23
D_a	22
KBRG	6101
SRIX	0.01
Noun	Bearing
yobi	6802
SDM_	19.5
bomp	0
SRIN	-0.01
mass	0.007
SREX	0.01
Bore	0.591 Inch   15 Millimeter
SBRG	18
SREN	-0.01

ALPHA_	0
UNSPSC	31171504
da max	17 mm
LangID	1
r min.	0,3 mm
C_conv	2070
Weight	0,007 Kg
da min	17
GRS rpm	28000
Oil rpm	34000
hidYobi	6802
da min.	17 mm
Da max.	22 mm
ra max.	0,3 mm
Category	Single Row Ball Bearing
hidTable	ecat_NSRDGB
Inventory	0.0
Snap Ring	No
Size (mm)	15x24x5
Enclosure	Open
bore type:	Round
Prod_Type3	DGBB_SR_OT
Width (mm)	5
Weight / LBS	0.007
maximum rpm:	34000 rpm
Product Group	B00308
closure type:	Open
Cage Material	Steel
Inch - Metric	Metric
Bearing number	6802
bore diameter:	15 mm
cage material:	Steel Cage

overall width:	5 mm
Keyword String	Ball
finish/coating:	Uncoated
Precision Class	ABEC 1   ISO P0
Rolling Element	Ball Bearing
Outside Diameter	0.945 Inch   24 Millimeter
Manufacturer URL	<a href="http://www.nskamericas.com">http://www.nskamericas.com</a>
Long Description	15MM Bore; 24MM Outside Diameter; 5MM Outer Race Diameter; Open; Ball Bearing; ABEC 1   ISO P0; No Filling Slot; No Snap Ring; No Internal Special Features
Outer Race Width	0.197 Inch   5 Millimeter
Weight / Kilogram	0.007
Manufacturer Name	NSK
precision rating:	ABEC1, P0
outside diameter:	24 mm
Internal Clearance	C0-Medium
Bore Diameter (mm)	15
snap ring included:	Without Snap Ring
Outer Diameter (mm)	24
internal clearance:	C0
Minimum Buy Quantity	N/A
row type & fill slot:	Single Row Non-Fill Slot
dynamic load capacity:	2070 N
Harmonized Tariff Code	8482.10.50.68
(Oil) Lubrication Speed	34 000 r/min
Manufacturer Item Number	6802
Internal Special Features	No

(Grease) Lubrication Speed	28 000 r/min
Basic static load rating (C0)	1,26 kN
Basic dynamic load rating (C)	2,07 kN
Maximum Capacity / Filling Slot	No