



Bearing No. 6802LLB

D	24 mm
d	15 mm
B	5 mm
C	5 mm
Bore	0.591 Inch 15 Millimeter
Noun	Bearing
Weight	0,007 Kg
da max	17,5 mm
r min.	0,3 mm
UNSPSC	31171504
ra max.	0,3 mm
da min.	17 mm
Da max.	22 mm
Category	Single Row Ball Bearing
Snap Ring	No
Enclosure	2 Seals
Inventory	4.0
Size (mm)	15x24x5
Width (mm)	5
bore type:	Round
Weight / LBS	0.016
Product Group	B00308
Inch - Metric	Metric
closure type:	Double Sealed
Cage Material	Steel
overall width:	5 mm
Enclosure Type	Non-Contact Seal
Keyword String	Ball
Bearing number	6802LLB

bore diameter:	15 mm
fillet radius:	0.3 mm
cage material:	Steel
Precision Class	ABEC 1 ISO P0
Rolling Element	Ball Bearing
finish/coating:	Uncoated
Long Description	15MM Bore; 24MM Outside Diameter; 5MM Outer Race Diameter; 2 Seals; Ball Bearing; ABEC 1 ISO P0; No Filling Slot; No Snap Ring; No Internal Special Features
Manufacturer URL	http://www.ntnamerica.com
Outer Race Width	0.197 Inch 5 Millimeter
Outside Diameter	0.945 Inch 24 Millimeter
outside diameter:	24 mm
Weight / Kilogram	0.007
bearing material:	High Carbon Chrome Steel
Manufacturer Name	NTN
inner ring width:	5 mm
precision rating:	ISO Class 0
outer ring width:	5 mm
Internal Clearance	C0-Medium
Bore Diameter (mm)	15
internal clearance:	CN
snap ring included:	Without Snap Ring
Outer Diameter (mm)	24
Minimum Buy Quantity	N/A
static load capacity:	1260 N
maximum rpm (grease):	26000 rpm

row type & fill slot:	Single Row Non-Fill Slot
Harmonized Tariff Code	8482.10.50.68
dynamic load capacity:	2080 N
Manufacturer Item Number	6802LLB/2AS
Internal Special Features	No
manufacturer product page:	Click here
(Grease) Lubrication Speed	26 000 r/min
operating temperature range:	-40 to 120 °C
Basic static load rating (C0)	1,26 kN
Basic dynamic load rating (C)	2,08 kN
Maximum Capacity / Filling Slot	No