



Bearing No. 6802LLU

D	24 mm
d	15 mm
B	5 mm
C	5 mm
Bore	0.591 Inch 15 Millimeter
Noun	Bearing
da max	17,5 mm
UNSPSC	31171504
r min.	0,3 mm
Weight	0,007 Kg
ra max.	0,3 mm
da min.	17 mm
Da max.	22 mm
Category	Single Row Ball Bearing
Snap Ring	No
Size (mm)	15x24x5
Enclosure	2 Seals
Inventory	0.0
Width (mm)	5
Weight / LBS	0.015
Product Group	B00308
Inch - Metric	Metric
Cage Material	Steel
Enclosure Type	Contact Seal
Other Features	Deep Groove Double Lip Friction Nitrile Rubber Seal -20 To 120 Deg C
Keyword String	Ball
Bearing number	6802LLU

Rolling Element	Ball Bearing
Reference speed	17 000 r/min
Precision Class	ABEC 1 ISO P0
Inner Race Width	0 Inch 0 Millimeter
Outer Race Width	0.197 Inch 5 Millimeter
Manufacturer URL	http://www.ntnamerica.com
Outside Diameter	0.945 Inch 24 Millimeter
Long Description	15MM Bore; 24MM Outside Diameter; 5MM Outer Race Width; 2 Seals; Ball Bearing; ABEC 1 ISO P0; No Filling Slot; No Snap Ring; No Internal Special Features; C0-Medium Internal Clearance; Steel Cage; C
Manufacturer Name	NTN
Weight / Kilogram	0
Internal Clearance	C0-Medium
Bore Diameter (mm)	15
Outer Diameter (mm)	24
Minimum Buy Quantity	N/A
Harmonized Tariff Code	8482.10.50.68
Manufacturer Item Number	6802LLU
Internal Special Features	No
Basic static load rating (C0)	1,26 kN
Basic dynamic load rating (C)	2,08 kN
Maximum Capacity / Filling Slot	No

