



Bearing No. 6802ZZ

C	5 mm
d	15 mm
D	24 mm
B	5 mm
Noun	Bearing
Bore	0.591 Inch 15 Millimeter
da max	17,5 mm
Weight	0,007 Kg
UNSPSC	31171504
r min.	0,3 mm
Da max.	22 mm
ra max.	0,3 mm
da min.	17 mm
series:	68
Category	Single Row Ball Bearing
Size (mm)	15x24x5
Enclosure	2 Metal Shields
Inventory	0.0
Snap Ring	No
bore type:	Round
Width (mm)	5
Weight / LBS	0.015
maximum rpm:	26000 RPM
closure type:	Double Shielded
Product Group	B00308
Inch - Metric	Metric
Cage Material	Steel
Bearing number	6802ZZ
overall width:	5 mm

bore diameter:	15 mm
cage material:	Steel
fillet radius:	0.3 mm
Keyword String	Ball
Rolling Element	Ball Bearing
Precision Class	ABEC 1 ISO P0
finish/coating:	Uncoated
Outside Diameter	0.945 Inch 24 Millimeter
Outer Race Width	0.197 Inch 5 Millimeter
Long Description	15MM Bore; 24MM Outside Diameter; 5MM Outer Race Diameter; 2 Metal Shields; Ball Bearing; ABEC 1 ISO P0; No Filling Slot; No Snap Ring; No Internal Special Features
Manufacturer URL	http://www.ntnamerica.com
bearing material:	High Carbon Chrome Steel
outside diameter:	24 mm
inner ring width:	5 mm
Manufacturer Name	NTN
Weight / Kilogram	0.007
outer ring width:	5 mm
precision rating:	ISO Class 0
Bore Diameter (mm)	15
Internal Clearance	C0-Medium
snap ring included:	Without Snap Ring
Outer Diameter (mm)	24
internal clearance:	CN
Minimum Buy Quantity	N/A
static load capacity:	1260 N

maximum rpm (grease):	26000 rpm
row type & fill slot:	Single Row Non-Fill Slot
dynamic load capacity:	2080 N
Harmonized Tariff Code	8482.10.50.68
Manufacturer Item Number	6802ZZ/2AS
Internal Special Features	No
manufacturer product page:	Click here
(Grease) Lubrication Speed	26 000 r/min
operating temperature range:	-40 to 120 °C
Basic dynamic load rating (C)	2,08 kN
Basic static load rating (C0)	1,26 kN
Maximum Capacity / Filling Slot	No