



### Bearing No. 6801LLU

C	5 mm
d	12 mm
D	21 mm
B	5 mm
Bore	0.472 Inch   12 Millimeter
Noun	Bearing
Weight	0,006 Kg
da max	14,5 mm
UNSPSC	31171504
r min.	0,3 mm
da min.	14 mm
ra max.	0,3 mm
series:	68
Da max.	19 mm
Category	Single Row Ball Bearing
Enclosure	2 Seals
Size (mm)	12x21x5
Inventory	0.0
Snap Ring	No
Width (mm)	5
bore type:	Round
maximum rpm:	20000 RPM
Weight / LBS	0.013
Cage Material	Steel
Inch - Metric	Metric
closure type:	Double Sealed
Product Group	B00308
bore diameter:	12 mm
Keyword String	Ball

overall width:	5 mm
cage material:	Steel
fillet radius:	0.3 mm
Bearing number	6801LLU
Enclosure Type	Contact Seal
Reference speed	20 000 r/min
finish/coating:	Uncoated
Rolling Element	Ball Bearing
Precision Class	ABEC 1   ISO P0
Outside Diameter	0.827 Inch   21 Millimeter
Manufacturer URL	<a href="http://www.ntnamerica.com">http://www.ntnamerica.com</a>
Long Description	12MM Bore; 21MM Outside Diameter; 5MM Outer Race Diameter; 2 Seals; Ball Bearing; ABEC 1   ISO P0; No Filling Slot; No Snap Ring; No Internal Special Features
Outer Race Width	0.197 Inch   5 Millimeter
outside diameter:	21 mm
precision rating:	ISO Class 0
bearing material:	High Carbon Chrome Steel
Weight / Kilogram	0.006
inner ring width:	5 mm
outer ring width:	5 mm
Manufacturer Name	NTN
Bore Diameter (mm)	12
Internal Clearance	C0-Medium
internal clearance:	CN
snap ring included:	Without Snap Ring
Outer Diameter (mm)	21

Minimum Buy Quantity	N/A
row type & fill slot:	Single Row Non-Fill Slot
maximum rpm (grease):	20000 rpm
static load capacity:	1040 N
dynamic load capacity:	1920 N
Harmonized Tariff Code	8482.10.50.68
Manufacturer Item Number	6801LLU/2AS
Internal Special Features	No
manufacturer product page:	<a href="#">Click here</a>
operating temperature range:	-40 to 120 °C
Basic static load rating (C0)	1,04 kN
Basic dynamic load rating (C)	1,92 kN
Maximum Capacity / Filling Slot	No