



Bearing No. 6704LLF

D	27 mm
d	20 mm
B	4 mm
C	4 mm
Bore	0.787 Inch 20 Millimeter
Noun	Bearing
UNSPSC	31171504
r min.	0,2 mm
da max	22,3 mm
Weight	0,0045 Kg
da min.	21,6 mm
Da max.	25,4 mm
ra max.	0,2 mm
Category	Single Row Ball Bearing
Enclosure	2 Seals
Inventory	0.0
Size (mm)	20x27x4
Snap Ring	No
bore type:	Round
Width (mm)	4
Product Group	B00308
Inch - Metric	Metric
Cage Material	Steel
closure type:	Double Sealed
Keyword String	Ball
bore diameter:	20 mm
overall width:	4 mm
cage material:	Stainless Steel
Other Features	Deep Groove

fillet radius:	0.2 mm
Bearing number	6704LLF
Enclosure Type	Non-Contact Seal
Rolling Element	Ball Bearing
Precision Class	ABEC 1 ISO P0
finish/coating:	Uncoated
Outer Race Width	0.157 Inch 4 Millimeter
Long Description	20MM Bore; 27MM Outside Diameter; 4MM Outer Race Width; 2 Seals; Ball Bearing; ABEC 1 ISO P0; No Filling Slot; No Snap Ring; No Internal Special Features; C0-Medium Internal Clearance; Steel Cage; N
Manufacturer URL	http://www.ntnamerica.com
Outside Diameter	1.063 Inch 27 Millimeter
Inner Race Width	0 Inch 0 Millimeter
outer ring width:	4 mm
inner ring width:	4 mm
bearing material:	High Carbon Chrome Steel
precision rating:	ISO Class 0
Manufacturer Name	NTN
outside diameter:	27 mm
Weight / Kilogram	0
Internal Clearance	C0-Medium
Bore Diameter (mm)	20
Outer Diameter (mm)	27
internal clearance:	CN
snap ring included:	Without Snap Ring

Minimum Buy Quantity	N/A
maximum rpm (grease):	5000 rpm
static load capacity:	730 N
row type & fill slot:	Single Row Non-Fill Slot
dynamic load capacity:	1040 N
Harmonized Tariff Code	8482.10.50.68
Manufacturer Item Number	6704LLF
Internal Special Features	No
(Grease) Lubrication Speed	5 000 r/min
manufacturer product page:	Click here
operating temperature range:	-40 to 140 °C
Basic dynamic load rating (C)	1,04 kN
Basic static load rating (C0)	0,73 kN
Maximum Capacity / Filling Slot	No