



Bearing No. 6706LLF

D	37 mm
d	30 mm
B	4 mm
C	4 mm
Bore	1.181 Inch 30 Millimeter
Noun	Bearing
UNSPSC	31171504
r min.	0,2 mm
da max	32,3 mm
Weight	0,006 Kg
da min.	31,6 mm
Da max.	35,4 mm
ra max.	0,2 mm
Category	Single Row Ball Bearing
Enclosure	2 Seals
Inventory	0.0
Size (mm)	30x37x4
Snap Ring	No
bore type:	Round
Width (mm)	4
Product Group	B00308
Inch - Metric	Metric
Cage Material	Steel
closure type:	Double Sealed
Keyword String	Ball
bore diameter:	30 mm
overall width:	4 mm
cage material:	Stainless Steel
Other Features	Deep Groove

fillet radius:	0.2 mm
Bearing number	6706LLF
Enclosure Type	Non-Contact Seal
Rolling Element	Ball Bearing
Precision Class	ABEC 1 ISO P0
finish/coating:	Uncoated
Outer Race Width	0.157 Inch 4 Millimeter
Long Description	30MM Bore; 37MM Outside Diameter; 4MM Outer Race Width; 2 Seals; Ball Bearing; ABEC 1 ISO P0; No Filling Slot; No Snap Ring; No Internal Special Features; C0-Medium Internal Clearance; Steel Cage; N
Manufacturer URL	http://www.ntnamerica.com
Outside Diameter	1.457 Inch 37 Millimeter
Inner Race Width	0 Inch 0 Millimeter
outer ring width:	4 mm
inner ring width:	4 mm
bearing material:	High Carbon Chrome Steel
precision rating:	ISO Class 0
Manufacturer Name	NTN
outside diameter:	37 mm
Weight / Kilogram	0.008
Internal Clearance	C0-Medium
Bore Diameter (mm)	30
Outer Diameter (mm)	37
internal clearance:	CN
snap ring included:	Without Snap Ring

Minimum Buy Quantity	N/A
maximum rpm (grease):	3300 rpm
static load capacity:	950 N
row type & fill slot:	Single Row Non-Fill Slot
dynamic load capacity:	1140 N
Harmonized Tariff Code	8482.10.50.68
Manufacturer Item Number	6706LLF
Internal Special Features	No
(Grease) Lubrication Speed	3 300 r/min
manufacturer product page:	Click here
operating temperature range:	-40 to 140 °C
Basic dynamic load rating (C)	1,14 kN
Basic static load rating (C0)	0,95 kN
Maximum Capacity / Filling Slot	No