



Bearing No. T4CB130

D	185 mm
d	130 mm
T	29 mm
B	27 mm
C	21 mm
a	37,5 mm
e	0.47
Cr	18600
Y0	0.7
db	141
da	148
Y1	1.3
B_	27
Sb	8
C0	296
Sa	8
D_	185
Z_	31
C_	21
C0r	30000
DA_	14.109
Iso	4CB
DE_	171.624
D_b	179
DI_	144.378
SBRG	4CB
SDM_	158.001
D_a2	171
KBRG	3111
yobi	T4CB130

D_a1	171
mass	2.32
TC-RA	294.8
r min.	3 mm
Weight	2,32 Kg
TC-DA1	14.576
TC-DA2	13.641
TC-SLR	19
Da min	171 mm
LangID	1
ALPHA_	17.5
Db min.	179 mm
Oil rpm	2400
db max.	141 mm
Da max.	171 mm
ra max.	2,5 mm
hidYobi	T4CB130
da min.	148 mm
T-ALP21	35
rb max.	2,5 mm
T-ALP22	0
T-ALP23	0
GRS rpm	1700
inner r	3
outer r	3
r1 min.	3 mm
hidTable	ecat_NSTPRM
TC-BET23	0
TC-BET21	2
inner ra	2.5
outer rb	2.5
TC-BET22	50

Size (mm)	130x185x29
Width (mm)	29
Prod_Type3	TRBSR_MD_A
Bearing number	T4CB130
Bore Diameter (mm)	130
Outer Diameter (mm)	185
Calculation factor (e)	0,47
Calculation factor (Y0)	0,7
(Oil) Lubrication Speed	2400 r/min
(Grease) Lubrication Speed	1700 r/min
Basic dynamic load rating (C)	183 kN
Basic static load rating (C0)	296 kN