



Bearing No. T4CB140

| | |
|---------|---------|
| C | 21 mm |
| e | 0.50 |
| d | 140 mm |
| D | 195 mm |
| T | 29 mm |
| B | 27 mm |
| a | 40,9 mm |
| Y0 | 0.66 |
| Y1 | 1.19 |
| Cu | 39.9 |
| Cr | 232 |
| C0r | 293 |
| a(mm) | 40.9 |
| r min. | 3 mm |
| da max | 151 mm |
| Da min | 180 mm |
| r(min) | 3 |
| Weight | 2,36 Kg |
| r1(min) | 3 |
| db(max) | 151 |
| da(min) | 154 |
| Sb(min) | 8 |
| Da(max) | 181 |
| Sa(min) | 5 |
| Da(min) | 180 |
| ra(max) | 2.5 |
| rb(max) | 2.5 |
| Db(min) | 189 |
| rb max. | 2,5 mm |
| ra max. | 2,5 mm |
| | |

| | |
|-------------------------------|------------|
| Db min. | 189 mm |
| Da max. | 181 mm |
| da min. | 154 mm |
| r2 min. | 3 mm |
| Oil lub. | 2300 |
| Size (mm) | 140x195x29 |
| Width (mm) | 29 |
| Bearing No. | T4CB140 |
| Grease lub. | 1700 |
| Bearing number | T4CB140 |
| (Refer.)Mass(kg) | 2.36 |
| Bore Diameter (mm) | 140 |
| Outer Diameter (mm) | 195 |
| Calculation factor (e) | 0,5 |
| Calculation factor (Y0) | 0,66 |
| (Oil) Lubrication Speed | 2300 r/min |
| (Grease) Lubrication Speed | 1700 r/min |
| Basic static load rating (C0) | 293 kN |
| Basic dynamic load rating (C) | 185 kN |