



Bearing No. 16030

D	225 mm
d	150 mm
B	24 mm
C	24 mm
r	1.1
Z_	18
B_	24
D_	225
ra	1
C0	91
fo	16.6
DI_	170.038
SRI	9.04
D_a	218.5
SRE	9.04
DA_	17.462
DE_	204.962
SRIN	-0.03
yobi	16030
SBRG	0
bomp	0
SREX	0.03
KBRG	6104
SDM_	187.5
mass	3.62
Bore	5.906 Inch 150 Millimeter
SREN	-0.03
SRIX	0.03
Noun	Bearing

C_conv	84000
da min	156.5
LangID	1
r min.	1,1 mm
UNSPSC	31171504
Weight	3,62 Kg
ALPHA_	0
GRS rpm	2600
hidYobi	16030
Da max.	218,5 mm
ra max.	1 mm
da min.	156,5 mm
Oil rpm	3000
Category	Single Row Ball Bearing
hidTable	ecat_NSRDGB
Size (mm)	150x225x24
Snap Ring	No
Enclosure	Open
Inventory	0.0
Width (mm)	24
Prod_Type3	DGBB_SR_OT
Weight / LBS	7.9821
Cage Material	Steel
Inch - Metric	Metric
Product Group	B00308
Bearing number	16030
Keyword String	Ball
Other Features	Deep Groove
Rolling Element	Ball Bearing
Precision Class	ABEC 1 ISO P0
Outside Diameter	8.858 Inch 225 Millimeter
Long Description	150MM Bore; 225MM

	Outside Diameter; 24MM Outer Race Width; Open; Ball Bearing; ABEC 1 ISO P0; No Filling Slot; No Snap Ring; No Internal Special Features; C0-Medium Internal Clearance; Steel Cage
Outer Race Width	0.945 Inch 24 Millimeter
Inner Race Width	0 Inch 0 Millimeter
Manufacturer URL	http://www.nskamericas.com
Manufacturer Name	NSK
Weight / Kilogram	3.6
Internal Clearance	C0-Medium
Bore Diameter (mm)	150
Outer Diameter (mm)	225
Minimum Buy Quantity	N/A
Harmonized Tariff Code	8482.10.50.68
(Oil) Lubrication Speed	3 000 r/min
Internal Special Features	No
(Grease) Lubrication Speed	2 600 r/min
Basic static load rating (C0)	91 kN
Basic dynamic load rating (C)	84 kN
Maximum Capacity / Filling Slot	No