



Bearing No. T4CB120

D	170 mm
d	120 mm
T	27 mm
B	25 mm
C	19,5 mm
a	35 mm
e	0.47
Cr	51600
Y0	0.7
db	129
da	138
Y1	1.3
B_	25
Sb	7.5
C0	243
Sa	7
D_	170
Z_	29
C_	19.5
C0r	24800
DA_	12.981
Iso	4CB
DE_	157.644
D_b	164
DI_	132.887
SBRG	4CB
SDM_	145.266
D_a2	158
KBRG	3111
yobi	T4CB120

D_a1	158
mass	1.78
TC-RA	271.488
r min.	3 mm
Weight	1,78 Kg
TC-DA1	13.424
TC-DA2	12.538
TC-SLR	18
Da min	158 mm
LangID	1
ALPHA_	17.5
Db min.	164 mm
Oil rpm	2600
db max.	129 mm
Da max.	158 mm
ra max.	2,5 mm
hidYobi	T4CB120
da min.	138 mm
T-ALP21	35
rb max.	2,5 mm
T-ALP22	0
T-ALP23	0
GRS rpm	1800
inner r	3
outer r	3
r1 min.	3 mm
hidTable	ecat_NSTPRM
TC-BET23	0
TC-BET21	2
inner ra	2.5
outer rb	2.5
TC-BET22	50

Size (mm)	120x170x27
Width (mm)	27
Prod_Type3	TRBSR_MD_A
Bearing number	T4CB120
Bore Diameter (mm)	120
Outer Diameter (mm)	170
Calculation factor (e)	0,47
Calculation factor (Y0)	0,7
(Oil) Lubrication Speed	2600 r/min
(Grease) Lubrication Speed	1800 r/min
Basic dynamic load rating (C)	153 kN
Basic static load rating (C0)	243 kN