



## Bearing No. 29296

H	103 mm
s	259 mm
d	480 mm
D	650 mm
C	53,5 mm
B	62,5 mm
D1	556 mm
B1	99 mm
d1	635 mm
Weight	98 Kg
ra max.	4 mm
r2 min.	5 mm
r1 min.	5 mm
Da max.	595 mm
da min.	570 mm
Size (mm)	480x650x53.5
Width (mm)	53,5
Mass bearing	98 kg
B <sub>1</sub>	99 mm
Limiting speed	900 r/min
Bearing number	29296
Reference speed	560 r/min
Bore Diameter (mm)	480
d <sub>a</sub> min.	570 mm
D <sub>a</sub> max.	595 mm
r <sub>a</sub> max.	4 mm
Outer Diameter (mm)	650
r <sub>1,2</sub> min.	5 mm
d <sub>1</sub> ?	635 mm
D <sub>1</sub> ?	556 mm

Fatigue load limit (Pu)	950
Basic dynamic load rating C	2350 kN
Minimum axial load factor A	13
Basic static load rating (C0)	11800 kN
Basic dynamic load rating (C)	2350 kN
Fatigue load limit P <sub>u</sub>	950 kN
Basic static load rating C <sub>0</sub>	11800 kN