



Bearing No. SS7203 CD/P4A

|                               |               |
|-------------------------------|---------------|
| D                             | 40 mm         |
| d                             | 17 mm         |
| B                             | 12 mm         |
| C                             | 12 mm         |
| a                             | 10 mm         |
| d1                            | 24,1 mm       |
| D1                            | 34,4 mm       |
| Weight                        | 0,065 Kg      |
| Db max                        | 37,6 mm       |
| db min                        | 21,2 mm       |
| r4 min.                       | 0,3 mm        |
| Da max.                       | 35,8 mm       |
| da min.                       | 21,2 mm       |
| r3 min.                       | 0,3 mm        |
| r2 min.                       | 0,6 mm        |
| r1 min.                       | 0,6 mm        |
| rb max.                       | 0,3 mm        |
| ra max.                       | 0,6 mm        |
| Size (mm)                     | 17x40x12      |
| Width (mm)                    | 12            |
| Bearing number                | SS7203 CD/P4A |
| Bore Diameter (mm)            | 17            |
| Outer Diameter (mm)           | 40            |
| Fatigue load limit (Pu)       | 0,176         |
| (Grease) Lubrication Speed    | 43 000 r/min  |
| Basic dynamic load rating (C) | 9,23 kN       |
| Basic static load rating (C0) | 4,15 kN       |