



Bearing No. 16052

| | |
|--------|---------|
| r | 3 |
| d | 260 mm |
| D | 400 mm |
| B | 44 mm |
| C | 44 mm |
| C0 | 310 |
| Z_ | 17 |
| ra | 2.5 |
| B_ | 44 |
| D_ | 400 |
| fo | 16.4 |
| D_a | 387 |
| SRE | 17.25 |
| DE_ | 363.338 |
| DA_ | 33.338 |
| DI_ | 296.662 |
| SRI | 17.25 |
| mass | 21.1 |
| SRIN | -0.065 |
| SBRG | 0 |
| SRIX | 0.065 |
| KBRG | 6104 |
| SREN | -0.065 |
| yobi | 16052 |
| bomp | 0 |
| SREX | 0.065 |
| SDM_ | 330 |
| r min. | 3 mm |
| ALPHA_ | 0 |
| da min | 273 |
| | |

| | |
|-------------------------------|-------------|
| C_conv | 237000 |
| Weight | 21,1 Kg |
| LangID | 1 |
| Oil rpm | 1700 |
| GRS rpm | 1400 |
| hidYobi | 16052 |
| ra max. | 2,5 mm |
| Da max. | 379 mm |
| da min. | 284 mm |
| hidTable | ecat_NSRDGB |
| Size (mm) | 260x400x44 |
| Prod_Type3 | DGBB_SR_OT |
| Width (mm) | 44 |
| Bearing number | 16052 |
| Bore Diameter (mm) | 260 |
| Outer Diameter (mm) | 400 |
| Basic static load rating (C0) | 310 kN |
| Basic dynamic load rating (C) | 237 kN |