



Bearing No. AXK0619TN

| | |
|-------------------|-----------------|
| D | 19 mm |
| d | 6 mm |
| T | 2 mm |
| Cu | 1.40 |
| D1 | - |
| Ca | 6.37 |
| Dw | 2 |
| Ea | 16.9 mm |
| Eb | 7.8 mm |
| Dc | 19 |
| C0a | 14.3 |
| Dc1 | 6 |
| D,d1 | 19 |
| a(mm) | - |
| h(mm) | - |
| h1(mm) | 1.00 |
| Weight | 0.001 Kg |
| ra(max) | 0.3 |
| ra max. | 0.3 mm |
| rs(min) | - |
| Category | Roller Bearings |
| Oil lub. | 23000 |
| Inventory | 0.0 |
| Size (mm) | 6x19x2 |
| Width (mm) | 2 |
| Bearing No. | AXK0619TN |
| Product Group | B04144 |
| Bearing number | AXK0619TN |
| (Refer.)Mass(kg) | - |
| Weight / Kilogram | 0 |

| | |
|---------------------------------------|---------|
| Manufacturer Name | KOYO |
| Washer designation | - |
| Bore Diameter (mm) | 6 |
| Outer Diameter (mm) | 19 |
| Minimum Buy Quantity | N/A |
| Basic static load rating (C0) | 14.3 kN |
| Basic dynamic load rating (C) | 6.37 kN |
| Washer designation Shaft piloted | - |
| Washer designation Housing piloted | - |