



Bearing No. NU 2338 ECML

s	9.5 mm
d	190 mm
D	400 mm
B	132 mm
F	240 mm
s max.	9.5 mm
Size (mm)	400x190x132
Width (mm)	132
Mass bearing	80.3 kg
D ₁	342.75 mm
Limiting speed	3100 r/min
Bearing number	NU 2338 ECML
Reference speed	1500 r/min
Limiting value e	0.3
d _a max.	234 mm
d _a min.	209 mm
Bore Diameter (mm)	400
r _a max.	4 mm
D _a max.	380 mm
r _b max.	4 mm
d _b min.	244 mm
Axial load factor Y	0.4
Outer Diameter (mm)	190
r _b - max.	4 mm
r _a - max.	4 mm
r _{1,2} min.	5 mm
d _a - min.	209 mm
D _a - max.	380 mm
d _b - min.	244 mm
d _a - max.	234 mm

$r_{3,4}$ min.	5 mm
D_1 ?	342.75 mm
$r_{3,4}$ - min.	5 mm
$r_{1,2}$ - min.	5 mm
Basic dynamic load rating C	1830 kN
Basic dynamic load rating - C	1830 kN
Fatigue load limit P_u	236 kN
Calculation factor k_r	0.38
Calculation factor - k_r	0.38
Fatigue load limit - P_u	236 kN
Basic static load rating C_0	2550 kN
Basic static load rating - C_0	2550 kN