



Bearing No. 22208-E1-K + H308

| | |
|----------------|---|
| | H308 / Adapter sleeve |
| e | 0,27 |
| D | 80 mm |
| B | 23 mm |
| l | 36 mm |
| c | 11 mm |
| m | 0,528 kg / Weight |
| d | 40 mm |
| Size (mm) | 35x80x23 |
| Width (mm) | 23 |
| m_1 | 0,19 kg |
| C_r | 101000 N / Dynamic load rating (radial) |
| n_s | 4,8 mm |
| d_s | 3,2 mm |
| n_B | 11800 N / Fatigue limit load, radial |
| d_2 | 48,8 mm |
| D_m | 58 mm |
| D_1 | 70,4 mm |
| Y_2 | 3,71 |
| Y_0 | 2,43 |
| n_G | 10500 1/min / Limiting speed |
| Y_1 | 2,49 |
| C_{Or} | 91000 N / Static load rating (radial) |
| Bearing number | 22208-E1-K + H308 |
| d_{1H} | 35 mm |
| | |

| | |
|---------------------|--------|
| r_{\min} | 1,1 mm |
| $r_{a \max}$ | 1 mm |
| $d_{a \max}$ | 48 mm |
| $D_{a \max}$ | 73 mm |
| $B_{a \min}$ | 5 mm |
| $d_{b \min}$ | 44 mm |
| Bore Diameter (mm) | 35 |
| Outer Diameter (mm) | 80 |