



Bearing No. SIR 120 ES

| | |
|-------------------|----------------------|
| G | M 130x3 |
| d | 120 mm |
| B | 85 mm |
| dk | 160 mm |
| h1 | 310 mm |
| ? | 6 ° |
| Angle | 6 ° |
| N max | 257 mm |
| C1 max | 90,5 mm |
| N max. | 257 mm |
| Weight | 84 Kg |
| N1 max | 86 mm |
| r1 min. | 1 mm |
| l7 min. | 138 mm |
| l4 max. | 493 mm |
| l3 min. | 135 mm |
| d4 max. | 175 mm |
| d2 max. | 343 mm |
| Category | Bearings |
| Inventory | 0.0 |
| Thread (G) | M 130x3 Tolerance 6H |
| Mass rod end | 76.6 kg |
| dk | 160 mm |
| h1 | 310 mm |
| Product Group | B04286 |
| Bearing number | SIR 120 ES |
| Weight / Kilogram | 90 |
| Manufacturer Name | SKF |
| d2 max. | 343 mm |
| r1 min. | 1 mm |
| | |

| | |
|--|-----------------------|
| Bore Diameter (mm) | 120 |
| d_4 max. | 175 mm |
| l_3 min. | 135 mm |
| l_4 max. | 493 mm |
| l_7 min. | 138 mm |
| C_1 max. | 90.5 mm |
| N_1 max. | 86 mm |
| Minimum Buy Quantity | N/A |
| Basic dynamic load rating C | 950 kN |
| Basic dynamic load rating (C) | 950 kN |
| Specific dynamic load factor K | 100 N/mm ² |
| Size bolt with internal hexagon | M 24 |
| Material constant K_M | 330 |
| Basic static load rating C_0 | 2450 kN |
| Tightening torque bolt with internal hexagon | 670 N·m |