



Bearing No. YET 204-012

D	47 mm
d	19.05 mm
C	14 mm
B	21.5 mm
Noun	Bearing
Bore	0.75 Inch 19.05 Millimeter
UNSPSC	31171536
series:	YET2
Category	Insert Bearings
Seal Type	M Seal
Size (mm)	47x19.05x31
Inventory	0.0
Snap Ring	No
bore type:	Round
Width (mm)	31
Weight / LBS	0.375
maximum rpm:	8500 RPM
Mass bearing	0.17 kg
B ₁	31 mm
Inch - Metric	Inch
s ₁	23.5 mm
Product Group	M06110
B ₄	4.75 mm
d ₂	32.4 mm
d ₁	28.2 mm
s ₁	24 mm
d ₂	32.4 mm
B ₄	4.75 mm
	30.5 mm

B¹

--	--

Keyword String	Insert
bore diameter:	0.7500 in
Bearing number	YET 204-012
Other Features	Single Row Standard Duty With Set Screw
Relubricatable	Yes
Mounting Method	Eccentric Collar
locking device:	Eccentric Collar
finish/coating:	Zinc Plated
Rolling Element	Ball Bearing
Outside Diameter	1.85 Inch 46.99 Millimeter
Long Description	3/4" Bore; Narrow Inner Ring; Ball Bearing; 1.221" Length Thru Bore; 0.551" Outer Race Width; 1.85" Outside Diameter; Relubricatable; M Seal Seal; Eccentric Collar Mounting Method
Manufacturer URL	http://www.skf.com
Outer Race Width	0.551 Inch 13.995 Millimeter
Length Thru Bore	1.221 Inch 31.013 Millimeter
inner ring width:	31 mm
outer ring width:	14 mm
outside diameter:	47 mm
bearing material:	Stainless Steel
Weight / Kilogram	0.173
Manufacturer Name	SKF
Inner Race Profile	Narrow Inner Ring
Outer Race Profile	Spherical
Bore Diameter (mm)	47
Outer Diameter (mm)	19,05

r _{1,2} min.	0.6 mm
Minimum Buy Quantity	N/A
Mass complete bearing	0.17 kg
d ₁ ?	28.2 mm
Harmonized Tariff Code	8482.10.50.00
r _{1,2} - min.	0.6 mm
Manufacturer Item Number	YET 204-012
Basic dynamic load rating C	12.7 kN
Limiting speed ¹⁾	8500 r/min
radial static load capacity:	6.55 kN
radial dynamic load capacity:	12.7 kN
Basic dynamic load rating - C	12.7 kN
Thread grub screw G ₂	1/4-28 UNF
Calculation factor f ₀	13
Fatigue load limit P _u	0.28 kN
Fatigue load limit - P _u	0.28 kN
Calculation factor - f ₀	13
Hexagonal key size for grub screw N	3.175 mm
Thread - G ₂ - 1/4-28 UNF	1/428 UNF
Hexagonal key size for grub screw - H	3.175 mm
Basic static load rating C ₀	6.55 kN
Limiting speed with shaft tolerance h6	8500 r/min
Basic static load rating - C ₀	6.6 kN
Recommended	4 N·m

tightening torque for grub screw	
-------------------------------------	--