



Bearing No. SILQG 125 ES

| | |
|---------------------|----------------------|
| B | 125 mm |
| d | 125 mm |
| G | M 100x3 |
| h1 | 260 mm |
| ? | 4 ° |
| dk | 160 mm |
| Angle | 4 ° |
| N max | 202 mm |
| N1 max | 75 mm |
| C1 max | 105 mm |
| Weight | 43 Kg |
| N max. | 202 mm |
| l4 max. | 407 mm |
| l7 min. | 118 mm |
| r1 min. | 1 mm |
| d4 max. | 135 mm |
| l3 min. | 113 mm |
| d2 max. | 268 mm |
| Thread (G) | M 100x3 Tolerance 6H |
| Mass rod end | 43 kg |
| h ₁ | 260 mm |
| d _k | 160 mm |
| Bearing number | SILQG 125 ES |
| C ₁ max. | 105 mm |
| Bore Diameter (mm) | 125 |
| d ₄ max. | 135 mm |
| l ₃ min. | 113 mm |
| l ₄ max. | 408 mm |
| l ₇ min. | 118 mm |
| N ₁ max. | 75 mm |

| | |
|----------------------------------------------|-----------------------|
| r_1 min. | 1 mm |
| d_2 max. | 268 mm |
| Basic dynamic load rating C | 950 kN |
| Basic dynamic load rating (C) | 950 kN |
| Specific dynamic load factor K | 100 N/mm ² |
| Size bolt with internal hexagon | M 24 |
| Material constant K_M | 330 |
| Basic static load rating C_0 | 1430 kN |
| Tightening torque bolt with internal hexagon | 670 N·m |