



Bearing No. 17TAB04DF-2LR

| | |
|-------------------------------|------------------|
| D | 47 mm |
| d | 17 mm |
| B | 15 mm |
| C | 15 mm |
| 2B | 30 mm |
| r1 | 0.6 mm |
| da2 | 26.8 mm |
| da1 | 33.7 mm |
| Da2 | 41.9 mm |
| Da1 | 35 mm |
| Width | 15 mm |
| Weight | 0.13 Kg |
| r min. | 1 mm |
| r1 min. | 0.6 mm |
| Size (mm) | 17x47x15 |
| Enclosure | Double Seal |
| Bore Type | Cylindrical Bore |
| Bore Size | 17 mm |
| Width (mm) | 15 |
| Configuration | Double Row |
| Bearing number | 17TAB04DF-2LR |
| Angle (?) | 60 ° |
| Outside Diameter | 47 mm |
| Static Load Rating | 7,200 N |
| Bore Diameter (mm) | 17 |
| Dynamic Load Rating | 5,800 N |
| Outer Diameter (mm) | 47 |
| Fillet Radius/Chamfer | 1 mm |
| Basic dynamic load rating (C) | 25,9 kN |
| | |

| | |
|----------------------------------|-------|
| Basic static load rating (C0) | 32 kN |
|----------------------------------|-------|