



Bearing No. SILJ 80 ES

| | |
|---------------------|---------------------|
| B | 55 mm |
| d | 80 mm |
| G | M 48x2 |
| h1 | 185 mm |
| ? | 6 ° |
| dk | 105 mm |
| Angle | 3 ° |
| N max | 156 mm |
| N1 max | 47 mm |
| C1 max | 47 mm |
| Weight | 14,5 Kg |
| N max. | 156 mm |
| l4 max. | 287,5 mm |
| l7 min. | 92 mm |
| r1 min. | 1 mm |
| d4 max. | 90 mm |
| l3 min. | 64 mm |
| d2 max. | 205 mm |
| Thread (G) | M 48x2 Tolerance 6H |
| Mass rod end | 14.5 kg |
| h ₁ | 185 mm |
| d _k | 105 mm |
| Bearing number | SILJ 80 ES |
| C ₁ max. | 47 mm |
| Bore Diameter (mm) | 80 |
| d ₄ max. | 90 mm |
| l ₃ min. | 64 mm |
| l ₄ max. | 287.5 mm |
| l ₇ min. | 92 mm |
| N ₁ max. | 47 mm |

| | |
|--|-----------------------|
| r_1 min. | 1 mm |
| d_2 max. | 205 mm |
| Basic dynamic load rating C | 400 kN |
| Basic dynamic load rating (C) | 400 kN |
| Specific dynamic load factor K | 100 N/mm ² |
| Size bolt with internal hexagon | M 20 |
| Material constant K_M | 330 |
| Basic static load rating C_0 | 610 kN |
| Tightening torque bolt with internal hexagon | 310 N·m |