



Bearing No. NU 2216 ECJ

s	1.4 mm
F	95.3 mm
d	80 mm
D	140 mm
B	33 mm
Noun	Bearing
Bore	3.15 Inch   80 Millimeter
Width	1.299 Inch   33 Millimeter
UNSPSC	31171547
s max.	1.4 mm
series:	NU22
Profile	Complete with Outer and Inner Ring
flanges:	(2) Outer Ring
Category	Cylindrical Roller Bearing
Retainer	Yes
Size (mm)	140x80x33
Snap Ring	No
Separable	Inner Ring - Both Sides
Inventory	0.0
bore type:	Straight
Width (mm)	33
maximum rpm:	5600 RPM
Weight / LBS	4.473
Bore Profile	Straight
Mass bearing	1.98 kg
closure type:	Open
Product Group	B04144
D <sub>1</sub>	121.7 mm

Cage Material	Steel
Inch - Metric	Metric
Bearing number	NU 2216 ECJ
Relubricatable	Yes
fillet radius:	2 mm
cage material:	Steel
Limiting speed	5600 r/min
bore diameter:	80 mm
Other Features	High Capacity   Plain Inner Ring   2 Rib Outer Ring   Cage on Outer Ring ID
overall width:	33 mm
number of rows:	1
Rolling Element	Cylindrical Roller Bearing
finish/coating:	Uncoated
Reference speed	5300 r/min
Precision Class	RBEC 1   ISO P0
Outside Diameter	5.512 Inch   140 Millimeter
Limiting value e	0.3
Long Description	80MM Bore; Straight Bore Profile; 140MM Outside Diameter; 33MM Width; Steel Cage Matetrial; RBEC 1   ISO P0; Single Row; Inner Ring - Both Sides Separable; No Snap Ring; Relubricatable; C0-Medium Inte
ring separation:	Separable Ring
Manufacturer URL	<a href="http://www.skf.com">http://www.skf.com</a>
Manufacturer Name	SKF
outer ring width:	33 mm

Weight / Kilogram	2.031
precision rating:	Not Rated
outside diameter:	140 mm
bearing material:	Steel
r <sub>b</sub> max.	2 mm
Internal Clearance	C0-Medium
r <sub>a</sub> max.	2 mm
D <sub>a</sub> max.	129.8 mm
d <sub>b</sub> min.	98 mm
d <sub>a</sub> max.	93 mm
d <sub>a</sub> min.	90 mm
Bore Diameter (mm)	140
Outer Diameter (mm)	80
internal clearance:	C0
Axial load factor Y	0.4
Minimum Buy Quantity	N/A
r <sub>a</sub> - max.	2 mm
d <sub>a</sub> - min.	90 mm
r <sub>b</sub> - max.	2 mm
d <sub>a</sub> - max.	93 mm
d <sub>b</sub> - min.	98 mm
D <sub>a</sub> - max.	129.8 mm
r <sub>1,2</sub> min.	2 mm
r <sub>3,4</sub> min.	2 mm
D <sub>1</sub> ?	121.7 mm
static load capacity:	245 kN
r <sub>3,4</sub> - min.	2 mm
Harmonized Tariff Code	8482.50.00.00
r <sub>1,2</sub> - min.	2 mm
dynamic load capacity:	212 kN
Manufacturer Item Number	NU 2216 ECJ
Number of Rows of	Single Row

Rollers	
Basic dynamic load rating C	212 kN
operating temperature range:	Maximum of +300 °F
Basic dynamic load rating - C	212 kN
Fatigue load limit $P_u$	31 kN
Calculation factor $k_r$	0.2
Fatigue load limit - $P_u$	31 kN
Calculation factor - $k_r$	0.2
Basic static load rating $C_0$	245 kN
Basic static load rating - $C_0$	245 kN