



### Bearing No. 2217-M

|                     |                                        |
|---------------------|----------------------------------------|
| e                   | 0,26                                   |
| m                   | 2,79 kg / Weight                       |
| d                   | 85 mm                                  |
| D                   | 150 mm                                 |
| B                   | 36 mm                                  |
| Size (mm)           | 85x150x36                              |
| Width (mm)          | 36                                     |
| $C_r$               | 59000 N / Dynamic load rating (radial) |
| $Y_2$               | 3,81                                   |
| $D_1$               | 130 mm                                 |
| $d_1$               | 105,2 mm                               |
| $Y_0$               | 2,58                                   |
| $Y_1$               | 2,46                                   |
| $n_G$               | 7000 1/min / Limiting speed            |
| $n_B$               | 5800 1/min / Reference speed           |
| $C_{0r}$            | 23400 N / Static load rating (radial)  |
| Bearing number      | 2217-M                                 |
| $C_{ur}$            | 1340 N / Fatigue limit load, radial    |
| $r_{min}$           | 2 mm                                   |
| $d_{a min}$         | 96 mm                                  |
| $D_{a max}$         | 139 mm                                 |
| $r_{a max}$         | 2 mm                                   |
| Bore Diameter (mm)  | 85                                     |
| Outer Diameter (mm) | 150                                    |