




Bearing No. NU 216 ECJ

s	1.4 mm
F	95.3 mm
d	80 mm
D	140 mm
B	26 mm
Noun	Bearing
Bore	3.15 Inch 80 Millimeter
Width	1.024 Inch 26 Millimeter
UNSPSC	31171547
s max.	1.4 mm
series:	NU2
Profile	Complete with Outer and Inner Ring
flanges:	(2) Outer Ring
Category	Cylindrical Roller Bearing
Retainer	Yes
Size (mm)	140x80x26
Snap Ring	No
Separable	Inner Ring - Both Sides
Inventory	0.0
bore type:	Straight
Width (mm)	26
maximum rpm:	5600 RPM
Weight / LBS	3.507
Bore Profile	Straight
Mass bearing	1.55 kg
closure type:	Open
Product Group	B04144
D ₁	121.7 mm

Cage Material	Steel
Inch - Metric	Metric
Bearing number	NU 216 ECJ
Relubricatable	Yes
fillet radius:	2 mm
cage material:	Steel
Limiting speed	5600 r/min
bore diameter:	80 mm
Other Features	High Capacity Plain Inner Ring 2 Rib Outer Ring Cage on Outer Ring ID
overall width:	26 mm
number of rows:	1
Rolling Element	Cylindrical Roller Bearing
finish/coating:	Uncoated
Reference speed	5300 r/min
Precision Class	RBEC 1 ISO P0
Outside Diameter	5.512 Inch 140 Millimeter
Limiting value e	0.2
Long Description	80MM Bore; Straight Bore Profile; 140MM Outside Diameter; 26MM Width; Steel Cage Matetrial; RBEC 1 ISO P0; Single Row; Inner Ring - Both Sides Separable; No Snap Ring; Relubricatable; C0-Medium Inte
ring separation:	Separable Ring
Manufacturer URL	http://www.skf.com
Manufacturer Name	SKF
outer ring width:	26 mm

Weight / Kilogram	1.592
precision rating:	Not Rated
outside diameter:	140 mm
bearing material:	Steel
r _b max.	2 mm
Internal Clearance	C0-Medium
r _a max.	2 mm
D _a max.	129.8 mm
d _b min.	98 mm
d _a max.	93 mm
d _a min.	90 mm
Bore Diameter (mm)	140
Outer Diameter (mm)	80
internal clearance:	C0
Axial load factor Y	0.6
Minimum Buy Quantity	N/A
r _a - max.	2 mm
d _a - min.	90 mm
r _b - max.	2 mm
d _a - max.	93 mm
d _b - min.	98 mm
D _a - max.	129.8 mm
r _{1,2} min.	2 mm
r _{3,4} min.	2 mm
D ₁ ?	121.7 mm
static load capacity:	166 kN
r _{3,4} - min.	2 mm
Harmonized Tariff Code	8482.50.00.00
r _{1,2} - min.	2 mm
dynamic load capacity:	160 kN
Manufacturer Item Number	NU 216 ECJ
Number of Rows of	Single Row

Rollers	
Basic dynamic load rating C	160 kN
operating temperature range:	Maximum of +300 °F
Basic dynamic load rating - C	160 kN
Fatigue load limit P_u	21.2 kN
Calculation factor k_r	0.15
Fatigue load limit - P_u	21.2 kN
Calculation factor - k_r	0.15
Basic static load rating C_0	166 kN
Basic static load rating - C_0	166 kN