



Bearing No. NU 2032 ECMA

s	3 mm
d	160 mm
D	240 mm
B	48 mm
F	179 mm
s max.	3 mm
Size (mm)	240x160x48
Width (mm)	48
Mass bearing	8.09 kg
$D_1$	216 mm
Limiting speed	4000 r/min
Bearing number	NU 2032 ECMA
Reference speed	2600 r/min
Limiting value e	0.3
$d_a$ max.	177 mm
$d_a$ min.	167 mm
Bore Diameter (mm)	240
$r_a$ max.	2 mm
$D_a$ max.	230 mm
$r_b$ max.	1.5 mm
$d_b$ min.	183 mm
Axial load factor Y	0.4
Outer Diameter (mm)	160
$r_b$ - max.	1.5 mm
$r_a$ - max.	2 mm
$r_{1,2}$ min.	2.1 mm
$d_a$ - min.	167 mm
$D_a$ - max.	230 mm
$d_b$ - min.	183 mm
$d_a$ - max.	177 mm

$r_{3,4}$ min.	1.5 mm
$D_1$ ?	216 mm
$r_{3,4}$ - min.	1.5 mm
$r_{1,2}$ - min.	2.1 mm
Basic dynamic load rating C	418 kN
Basic dynamic load rating - C	418 kN
Fatigue load limit $P_u$	72 kN
Calculation factor $k_r$	0.2
Calculation factor - $k_r$	0.2
Fatigue load limit - $P_u$	72 kN
Basic static load rating $C_0$	670 kN
Basic static load rating - $C_0$	670 kN