



Bearing No. SIJK22C

| | |
|---|-------------------------|
| Width (B) | 28.0000 |
| Width (mm) | 28 |
| Weight (g) | 610.00 |
| Bore Dia (d) | 22.0000 |
| Bearing number | SIJK22C |
| Body Dia. (d3) | 30.000 |
| Thread Size (G) | M22 X 1.5 |
| Radius (min) (rs) | 0.600 |
| Bore Diameter (mm) | 22 |
| Rod End Width (d2) | 56.000 |
| Body End Dia. (d4) | 37.000 |
| Thread Length (l1) | 33.000 |
| Body End Flats (W) | 34.000 |
| Body End Width (l5) | 12.000 |
| Rod End Thickness (C1) | 21.000 |
| Rod Overall Length (l2) | 112.000 |
| Bore Center to Body (l7) | 28 |
| Static Load Rating (Cor) | 50,000 |
| Dynamic Load Rating (Cr) | 42,000 |
| Mis-alignment Angle (a deg.) | 14 |
| Bore Center to End of Rod (h) | 84.000 |
| Spherical Diameter (dk or Dk) | 38.100 |
| Bearing Type - steel-on-PTFE composite | steel on PTFE composite |
| Material - Body - Carbon steel-zinc plated, Ball - Hardened chrome steel-chrome plated, Liner | PTFE composite material |