



**Bearing No. NU 1064 MP**

s	9.7 mm
d	320 mm
D	480 mm
B	74 mm
F	360 mm
s max.	9.7 mm
Size (mm)	480x320x74
Width (mm)	74
Mass bearing	48.5 kg
D <sub>1</sub>	422 mm
Limiting speed	2200 r/min
Bearing number	NU 1064 MP
Reference speed	1400 r/min
Limiting value e	0.2
Bore Diameter (mm)	480
r <sub>a</sub> max.	3 mm
D <sub>a</sub> max.	465 mm
d <sub>b</sub> min.	364 mm
d <sub>a</sub> max.	355 mm
d <sub>a</sub> min.	335 mm
Axial load factor Y	0.6
Outer Diameter (mm)	320
d <sub>a</sub> - max.	355 mm
d <sub>a</sub> - min.	335 mm
r <sub>a</sub> - max.	3 mm
r <sub>1,2</sub> min.	4 mm
D <sub>a</sub> - max.	465 mm
d <sub>b</sub> - min.	364 mm
D <sub>1</sub> ?	422 mm
r <sub>1,2</sub> - min.	4 mm

Basic dynamic load rating C	880 kN
Basic dynamic load rating - C	880 kN
Fatigue load limit $P_u$	132 kN
Calculation factor $k_r$	0.1
Calculation factor - $k_r$	0.1
Fatigue load limit - $P_u$	132 kN
Basic static load rating $C_0$	1430 kN
Basic static load rating - $C_0$	1430 kN