



Bearing No. PSL 69-301

|                               |                       |
|-------------------------------|-----------------------|
| C                             | 23,02 mm              |
| a                             | 34 mm                 |
| d                             | 146,05 mm             |
| D                             | 193,675 mm            |
| T                             | 28,575 mm             |
| B                             | 28,575 mm             |
| Da min                        | 176 mm                |
| da max                        | 155 mm                |
| r min.                        | 4,8 mm                |
| db min                        | 162 mm                |
| Weight                        | 2,31 Kg               |
| Db min.                       | 187 mm                |
| r2 min.                       | 1,5 mm                |
| ra max.                       | 1,5 mm                |
| Da max.                       | 182 mm                |
| r3 min.                       | 0,6 mm                |
| Size (mm)                     | 146.05x193.675x28.575 |
| Width (mm)                    | 28,575                |
| Bearing number                | PSL 69-301            |
| Bore Diameter (mm)            | 146,05                |
| Outer Diameter (mm)           | 193,675               |
| Calculation factor (e)        | 0,37                  |
| Calculation factor (Y)        | 1,63                  |
| (Oil) Lubrication Speed       | 2200 r/min            |
| (Grease) Lubrication Speed    | 1700 r/min            |
| Basic dynamic load rating (C) | 181 kN                |
| Basic static load rating (C0) | 390 kN                |