



Bearing No. FYR 2-18

S	0.794 mm
B	73.025 mm
s	25.4 mm
A	57.15 mm
L	177.8 mm
J	146.05 mm
a	3.175 mm
Bore	2 Inch 50.8 Millimeter
Noun	Bearing
Seals	Labyrinth
UNSPSC	31171501
Category	Flange Block
Inventory	0.0
Size (mm)	50.8x73.819x57.15
Width (mm)	57,15
Bolt Spacing	4.1 Inch 104.1 Millimeter
Weight / LBS	10.5
Housing Style	4 Bolt Round Flange Block
N ₁	14.287 mm
A ₆	19.05 mm
Product Group	M06288
A ₅	27.781 mm
d _a	50.8 mm
d ₂	73.819 mm
N ₁	14.288 mm
A ₆	19.05 mm
A ₅	27.781 mm
A ₃	20.638 mm

A ₁	75.406 mm
d ₂	73.819 mm
d _a	50.8 mm
A ₁	75.406 mm
A ₃	20.637 mm
Inch - Metric	Inch
Keyword String	Flanged
Other Features	Double Row Heavy Duty Open End With Set Screw
Bearing number	FYR 2-18
Limiting speed	5000 r/min
Relubricatable	Yes
Mounting Bolts	1/2 Inch
Rolling Element	Spherical Roller Bearing
Mounting Method	Concentric Collar
Long Description	4 Bolt Round Flange Block; 2" Bore; 5.8" Bolt Circle; 4.1" Bolt Spacing; 1 Piece Solid; Concentric Collar Mount; Cast Iron; Spherical Roller Bearing; 2-7/8" Length Thru Bore; Relub
Housing Material	Cast Iron
Manufacturer URL	http://www.skf.com
Length Thru Bore	2.875 Inch 73.02 Millimeter
Manufacturer Name	SKF
Weight / Kilogram	4.77
Mass bearing unit	4.76 kg
Insert Part Number	22210
Bore Diameter (mm)	50,8
Outer Diameter (mm)	73,819
Pilot Configuration	No Pilot

Minimum Buy Quantity	N/A
Housing Configuration	1 Piece Solid
Cartridge Pilot Depth	0 Inch 0 Millimeter
Harmonized Tariff Code	8483.20.40.80
Cartridge Pilot Diameter	0 Inch 0 Millimeter
Manufacturer Item Number	FYR 2-18
Number of Mounting Holes	4
Expansion / Non-expansion	Expansion
Attachment bolt diameter G	12.7 mm
Basic dynamic load rating C	84.5 kN
Basic dynamic load rating - C	84.5 kN
Nominal Bolt Circle Diameter Round	5.8 Inch 148 Millimeter