



**Bearing No. SL024832**

	NNCL4832V / Designation to DIN 5412
E	186,9 mm
m	3 kg / Weight
d	160 mm
D	200 mm
B	40 mm
C	20 mm
s	2 mm / Axial displacement
Bore	6.299 Inch   160 Millimeter
Noun	Bearing
Width	1.575 Inch   40 Millimeter
UNSPSC	31171547
Profile	Complete with Outer and Inner Ring
Retainer	No
Category	Cylindrical Roller Bearing
Size (mm)	160x200x40
Inventory	0.0
Snap Ring	No
Separable	Outer Ring - Both Sides
Width (mm)	40
Weight / LBS	7.92
Bore Profile	Straight
Cage Material	None
Product Group	B04144
Inch - Metric	Metric
$n_G$	1800 1/min / Limiting

	speed
d <sub>1</sub>	173,7 mm
C <sub>r</sub>	237000 N / Dynamic load rating (radial)
Relubricatable	Yes
Other Features	Full Complement   3 Rib Inner Ring   Plain Outer Ring   Operating Temperature From -30 to 120 Deg
Bearing number	SL024832
C <sub>ur</sub>	64000 N / Fatigue limit load, radial
C <sub>0r</sub>	560000 N / Static load rating (radial)
r <sub>min</sub>	1,1 mm
Rolling Element	Cylindrical Roller Bearing
Precision Class	RBEC 1   ISO P0
Long Description	160MM Bore; Straight Bore Profile; 200MM Outside Diameter; 40MM Width; RBEC 1   ISO P0; Double Row; Outer Ring - Both Sides Separable; No Snap Ring; Relubricatable; C0-Medium Internal Clearance; No Re
Manufacturer URL	<a href="http://www.ina.com">http://www.ina.com</a>
Outside Diameter	7.874 Inch   200 Millimeter
Weight / Kilogram	3
Manufacturer Name	SCHAEFFLER GROUP
Internal Clearance	C0-Medium
Bore Diameter (mm)	160
Outer Diameter (mm)	200

Minimum Buy Quantity	N/A
Harmonized Tariff Code	8482.50.00.00
Manufacturer Item Number	SL024832
Number of Rows of Rollers	Double Row