



Bearing No. 2211-K-TVH-C3 + H311

| | |
|----------------|---|
| | H311 / Adapter sleeve |
| d | 55 mm |
| m | 0,73 kg / Weight |
| e | 0,22 |
| D | 100 mm |
| B | 25 mm |
| l | 45 mm |
| c | 13 mm |
| Size (mm) | 50x100x25 |
| Width (mm) | 25 |
| m_1 | 0,35 kg / Weight, adapter sleeve |
| Y_1 | 2,92 |
| d_1 | 69,6 mm |
| Y_2 | 4,52 |
| D_m | 75 mm |
| C_r | 39000 N / Dynamic load rating (radial) |
| D_1 | 90 mm |
| Y_0 | 3,06 |
| n_G | 6700 1/min / Limiting speed |
| n_B | 7500 1/min / Reference speed |
| C_{0r} | 12400 N / Static load rating (radial) |
| Bearing number | 2211-K-TVH-C3 + H311 |
| C_{ur} | 770 N / Fatigue limit load, radial |
| d_{1H} | 50 mm |
| $r_{a \max}$ | 1,5 mm |

| | |
|---------------------|-------|
| $d_{b \text{ min}}$ | 60 mm |
| $D_{a \text{ max}}$ | 91 mm |
| $B_{a \text{ min}}$ | 10 mm |
| $d_{a \text{ max}}$ | 64 mm |
| Bore Diameter (mm) | 50 |
| Outer Diameter (mm) | 100 |