



Bearing No. FYTB 1.1/4 TF

J	130 mm
d	31.75 mm
A	34.5 mm
T	46.4 mm
L	96 mm
B	42.9 mm
H	14 mm
N	14 mm
Category	Bearings
Size (mm)	31.75x34.5x13
Inventory	0.0
Width (mm)	13
N ₄	2 mm
J ₇	15 mm
A ₁	13 mm
D _N	6.5 mm
D _N	6.5 mm
J ₆	106 mm
G _N	1/4-28 SAE-LT
D _a	88.9 mm
Product Group	M06110
A ₃	3.2 mm
R ₁	22 mm
N ₄	2 mm
J ₇	15 mm
J ₆	106 mm
A ₅	22 mm
B ₄	6 mm
B ₄	6 mm

A ₅	22 mm
s ₁	25.4 mm
A ₁	13 mm
R _G	1/4-28 UNF
R ₁	22 mm
s ₁	25.4 mm
D _{b2}	96 mm
D _{b1}	88 mm
Bearing number	FYTB 1.1/4 TF
R _?	45 °
SW _N	7 mm
D _{b1}	88 mm
SW _N	7 mm
D _{b2}	96 mm
Limiting speed	5300 r/min
Housing material	Cast iron
Manufacturer Name	SKF
Mass bearing unit	1.25 kg
Weight / Kilogram	0
Bore Diameter (mm)	31,75
R _?	45 °
D _a - H11	88.9 mm
A ₃ - H14	3.2 mm
Outer Diameter (mm)	34,5
Minimum Buy Quantity	N/A
R _G - 1/4-28 UNF	1/428 UNF
Basic dynamic load rating C	25.5 kN
Basic dynamic load rating - C	25.5 kN
G _N - 1/4-28 SAE-LT	1/428 SAELT
Thread grub screw G ₂	5/16-24 UNF

Fatigue load limit P_u	0.655 kN
Fatigue load limit - P_u	0.655 kN
Hexagonal key size for grub screw N	3.969 mm
Thread - G_2 - 5/16-24 UNF	5/1624 UNF
Hexagonal key size for grub screw - H	3.969 mm
Basic static load rating C_0	15.3 kN
Basic static load rating - C_0	15.3 kN
Recommended tightening torque for grub screw	6.5 N·m
Recommended diameter for attachment bolts, mm G	12 mm
Recommended diameter for attachment bolts, inch G	0.5 in