



Bearing No. FYTB 15 FM

N	11,5 mm
G	10 mm
T	39,1 mm
A	26 mm
L	57 mm
J	76,5 mm
H	98,5 mm
d	15 mm
B1	28,6 mm
A1	26 mm
s1	22,1 mm
Da	50,8 mm
A2	11 mm
Weight	0,42 Kg
Category	Bearings
Inventory	0.0
A <sub>1</sub>	11 mm
s <sub>1</sub>	22.6 mm
A <sub>3</sub>	3.2 mm
B <sub>1</sub>	28.6 mm
B <sub>4</sub>	4.75 mm
D <sub>a</sub>	50.8 mm
R <sub>1</sub>	19 mm
J <sub>7</sub>	11 mm
D <sub>N</sub>	6.5 mm
Product Group	M06110
G <sub>N</sub>	1/4-28 SAE-LT
J <sub>6</sub>	61.5 mm
R <sub>G</sub>	1/4-28 UNF
N <sub>4</sub>	2 mm

$R_?$	45 °
$SW_N$	7 mm
Limiting speed	9500 r/min
Bearing number	FYTB 15 FM
$D_{b1}$	50 mm
$D_{b2}$	57 mm
Housing material	Cast iron
Weight / Kilogram	0
Manufacturer Name	SKF
Mass bearing unit	0.36 kg
Bore Diameter (mm)	15
Minimum Buy Quantity	N/A
Fatigue load limit (Pu)	0,2
Basic dynamic load rating C	9.56 kN
Basic static load rating (C0)	4,75 kN
Basic dynamic load rating (C)	9,56 kN
Thread grub screw $G_2$	M6x0.75
Fatigue load limit $P_u$	0.2 kN
Hexagonal key size for grub screw N	3 mm
Basic static load rating $C_0$	4.75 kN
Recommended tightening torque for grub screw	4 N·m
Recommended diameter for attachment bolts, mm G	10 mm
Recommended diameter for attachment bolts, inch G	0.375 in