



Bearing No. FYTB 17 FM

L	57 mm
A	26 mm
d	17 mm
G	10 mm
H	98,5 mm
J	76,5 mm
N	11,5 mm
T	39,1 mm
Da	50,8 mm
s1	22,1 mm
A1	26 mm
B1	28,6 mm
A2	11 mm
Bore	0.669 Inch 17 Millimeter
Noun	Bearing
Seals	M Seal
Weight	0,41 Kg
UNSPSC	31171501
series:	FYTB
Category	Flange Block
Inventory	0.0
seal type:	Contact with Flinger
bore type:	Round
maximum rpm:	9500 RPM
Weight / LBS	0.904
Bolt Spacing	3.012 Inch 76.5 Millimeter
D _a	50.8 mm
Inch - Metric	Metric
A ₃	3.2 mm

A ₁	11 mm
D _N	6.5 mm
B ₁	28.6 mm
B ₄	4.75 mm
N ₄	2 mm
J ₇	11 mm
J ₆	61.5 mm
G _N	1/4-28 SAE-LT
Product Group	M06110
Housing Style	2 Bolt Flange Block
R ₁	19 mm
R _G	1/4-28 UNF
S ₁	22.6 mm
D _{b1}	50 mm
R _?	45 °
D _{b2}	57 mm
SW _N	7 mm
mounting type:	Two-Bolt Flange
Limiting speed	9500 r/min
bore diameter:	17 mm
Bearing number	FYTB 17 FM
Mounting Bolts	10 Millimeter
Other Features	Single Row Standard Duty Narrow Inner Race Open End Y Bearing
Relubricatable	Yes
Keyword String	Flanged
expansion type:	Non-Expansion Bearing (Fixed)
Mounting Method	Eccentric Collar
Rolling Element	Ball Bearing
locking device:	Eccentric Collar

finish/coating:	Uncoated
Long Description	2 Bolt Flange Block; 17MM Bore; 76MM Bolt Circle; 76.5MM Bolt Spacing; 1 Piece Solid; Eccentric Collar Mount; Cast Iron; Ball Bearing; 28.6MM Length Thru Bore; Relubricatable; M Seal Seals
Housing material	Cast iron
Manufacturer URL	http://www.skf.com
Length Thru Bore	1.126 Inch 28.6 Millimeter
Housing Material	Cast Iron
housing material:	Cast Iron
lubrication type:	Lubrication Fitting
Weight / Kilogram	0.41
Manufacturer Name	SKF
Mass bearing unit	0.34 kg
Insert Part Number	YET 203
Bore Diameter (mm)	17
Pilot Configuration	No Pilot
Minimum Buy Quantity	N/A
replacement bearing:	YET 203
length through bore:	39.1 mm
Cartridge Pilot Depth	0 Inch 0 Millimeter
Housing Configuration	1 Piece Solid
Harmonized Tariff Code	8483.20.40.40
Fatigue load limit (Pu)	0,2
Manufacturer Item Number	FYTB 17 FM
overall length/diameter:	57 mm
Cartridge Pilot Diameter	0 Inch 0 Millimeter
Number of Mounting Holes	2

manufacturer upc number:	7316577732439
Expansion / Non-expansion	Non-expansion
Basic dynamic load rating C	9.56 kN
radial static load capacity:	4.75 kN
Basic dynamic load rating (C)	9,56 kN
Basic static load rating (C0)	4,75 kN
bolt center-to-center length:	76.5 mm
radial dynamic load capacity:	9.56 kN
Thread grub screw G ₂	M6x0.75
Fatigue load limit P _u	0.2 kN
Nominal Bolt Circle Diameter Round	3 Inch 76 Millimeter
Hexagonal key size for grub screw N	3 mm
Basic static load rating C ₀	4.75 kN
Recommended tightening torque for grub screw	4 N·m
Recommended diameter for attachment bolts, mm G	10 mm
Recommended diameter for attachment bolts, inch G	0.375 in