



Bearing No. FYTB 25 WF

T	45,9 mm
G	10 mm
A	30 mm
N	11,5 mm
L	70 mm
H	124 mm
J	99 mm
d	25 mm
B1	44,4 mm
A1	30 mm
s1	26,9 mm
Da	63,5 mm
A2	12 mm
Weight	0,69 Kg
Category	Bearings
Inventory	0.0
A ₁	12 mm
A ₃	3.2 mm
s ₁	26.9 mm
A ₅	18 mm
B ₁	44.4 mm
B ₄	4.75 mm
D _a	63.5 mm
R ₁	20.5 mm
J ₇	12 mm
D _N	6.5 mm
Product Group	M06110
G _N	1/4-28 SAE-LT
J ₆	81 mm
R _G	1/4-28 UNF

N_4	2 mm
R_2	45 °
SW_N	7 mm
Limiting speed	7000 r/min
Bearing number	FYTB 25 WF
D_{b2}	70 mm
D_{b1}	65 mm
Housing material	Cast iron
Weight / Kilogram	0.568
Manufacturer Name	SKF
Mass bearing unit	0.63 kg
Bore Diameter (mm)	25
Minimum Buy Quantity	N/A
Fatigue load limit (P_u)	0,335
Basic dynamic load rating C	14 kN
Basic static load rating (C_0)	7,8 kN
Basic dynamic load rating (C)	14 kN
Thread grub screw G_2	M6x0.75
Fatigue load limit P_u	0.335 kN
Hexagonal key size for grub screw N	3 mm
Basic static load rating C_0	7.8 kN
Recommended tightening torque for grub screw	4 N·m
Recommended diameter for attachment bolts, mm G	10 mm
Recommended diameter for attachment bolts, inch G	0.375 in