



Bearing No. FYTB 30 TR

N	11,5 mm
G	10 mm
T	42,2 mm
A	32.5 mm
L	83 mm
J	116,5 mm
H	141,5 mm
B	38,1 mm
d	30 mm
A1	32,5 mm
s1	22,2 mm
Da	76,2 mm
A2	13 mm
Weight	0,93 Kg
Category	Bearings
Inventory	0.0
A ₁	13 mm
s ₁	22.2 mm
A ₃	3.2 mm
A ₅	20 mm
B ₄	5 mm
D _a	76.2 mm
R ₁	21 mm
J ₇	12.5 mm
D _N	6.5 mm
Product Group	M06110
G _N	1/4-28 SAE-LT
J ₆	98.5 mm
R _G	1/4-28 UNF
N ₄	2 mm

$R_?$	45 °
SW_N	7 mm
Limiting speed	3800 r/min
Bearing number	FYTB 30 TR
D_{b1}	77 mm
D_{b2}	83 mm
Housing material	Cast iron
Weight / Kilogram	0.2
Manufacturer Name	SKF
Mass bearing unit	0.84 kg
Bore Diameter (mm)	30
Minimum Buy Quantity	N/A
Fatigue load limit (Pu)	0,475
Basic dynamic load rating C	19.5 kN
Basic static load rating (C0)	11,2 kN
Basic dynamic load rating (C)	19,5 kN
Thread grub screw G_2	M6x0.75
Fatigue load limit P_u	0.475 kN
Hexagonal key size for grub screw N	3 mm
Basic static load rating C_0	11.2 kN
Recommended tightening torque for grub screw	4 N·m
Recommended diameter for attachment bolts, mm G	10 mm
Recommended diameter for attachment bolts, inch G	0.375 in