



Bearing No. FYTB 40 TR

T	54,2 mm
G	12 mm
A	38.5 mm
N	14 mm
L	102 mm
H	171,5 mm
J	143,5 mm
d	40 mm
B	49,2 mm
A1	38,5 mm
s1	30,2 mm
Da	88,9 mm
A2	14 mm
UNSPSC	31171501
Weight	1,65 Kg
Category	Bearings
Inventory	0.0
A ₁	14 mm
s ₁	30.2 mm
A ₃	3.2 mm
A ₅	23.5 mm
B ₄	8 mm
D _a	88.9 mm
R ₁	24.5 mm
J ₇	16 mm
D _N	6.5 mm
Product Group	M06110
G _N	1/4-28 SAE-LT
J ₆	115.5 mm
R _G	1/4-28 UNF

N_4	2 mm
R_2	45 °
SW_N	7 mm
Limiting speed	2800 r/min
Bearing number	FYTB 40 TR
D_{b1}	98 mm
D_{b2}	102 mm
Housing material	Cast iron
Weight / Kilogram	0
Manufacturer Name	SKF
Mass bearing unit	1.5 kg
Bore Diameter (mm)	40
Minimum Buy Quantity	N/A
Fatigue load limit (P_u)	0,8
Basic dynamic load rating C	30.7 kN
Basic static load rating (C_0)	19 kN
Basic dynamic load rating (C)	30,7 kN
Thread grub screw G_2	M8x1
Fatigue load limit P_u	0.8 kN
Hexagonal key size for grub screw N	4 mm
Basic static load rating C_0	19 kN
Recommended tightening torque for grub screw	6.5 N·m
Recommended diameter for attachment bolts, mm G	12 mm
Recommended diameter for attachment bolts, inch G	0.5 in