



Bearing No. FYTB 40 WF

| | |
|----------------|---------------|
| T | 58,9 mm |
| G | 12 mm |
| A | 38.5 mm |
| N | 14 mm |
| L | 102 mm |
| H | 171,5 mm |
| J | 143,5 mm |
| d | 40 mm |
| B1 | 56,3 mm |
| A1 | 38,5 mm |
| s1 | 34,9 mm |
| Da | 88,9 mm |
| A2 | 14 mm |
| Weight | 1,8 Kg |
| Category | Bearings |
| Inventory | 0.0 |
| A ₁ | 14 mm |
| A ₃ | 3.2 mm |
| s ₁ | 34.9 mm |
| A ₅ | 23.5 mm |
| B ₁ | 56.3 mm |
| B ₄ | 6.75 mm |
| D _a | 88.9 mm |
| R ₁ | 24.5 mm |
| J ₇ | 16 mm |
| D _N | 6.5 mm |
| Product Group | M06110 |
| G _N | 1/4-28 SAE-LT |
| J ₆ | 115.5 mm |
| R _G | 1/4-28 UNF |

| | |
|---|------------|
| N_4 | 2 mm |
| R_2 | 45 ° |
| SW_N | 7 mm |
| Limiting speed | 4800 r/min |
| Bearing number | FYTB 40 WF |
| D_{b2} | 102 mm |
| D_{b1} | 98 mm |
| Housing material | Cast iron |
| Weight / Kilogram | 0 |
| Manufacturer Name | SKF |
| Mass bearing unit | 1.65 kg |
| Bore Diameter (mm) | 40 |
| Minimum Buy Quantity | N/A |
| Fatigue load limit (P_u) | 0,8 |
| Basic dynamic load rating C | 30.7 kN |
| Basic static load rating (C_0) | 19 kN |
| Basic dynamic load rating (C) | 30,7 kN |
| Thread grub screw G_2 | M10x1 |
| Fatigue load limit P_u | 0.8 kN |
| Hexagonal key size for grub screw N | 5 mm |
| Basic static load rating C_0 | 19 kN |
| Recommended tightening torque for grub screw | 16.5 N·m |
| Recommended diameter for attachment bolts, mm G | 12 mm |
| Recommended diameter for attachment bolts, inch G | 0.5 in |