



Bearing No. NJ 2326 ECML

| | |
|-----------------------|--------------|
| D | 280 mm |
| d | 130 mm |
| B | 93 mm |
| F | 167 mm |
| s | 8.7 mm |
| s max. | 8.7 mm |
| UNSPSC | 31171547 |
| Category | Bearings |
| Inventory | 0.0 |
| Size (mm) | 280x130x93 |
| Width (mm) | 93 |
| Mass bearing | 29.5 kg |
| Product Group | B04144 |
| d ₁ | 181 mm |
| D ₁ | 235.2 mm |
| Limiting speed | 4500 r/min |
| Bearing number | NJ 2326 ECML |
| Reference speed | 2400 r/min |
| Limiting value e | 0.3 |
| Manufacturer Name | SKF |
| Weight / Kilogram | 0 |
| D _a max. | 261.4 mm |
| d _a max. | 163 mm |
| d _b min. | 184 mm |
| d _a min. | 147 mm |
| Bore Diameter (mm) | 280 |
| r _a max. | 3 mm |
| Outer Diameter (mm) | 130 |
| Axial load factor Y | 0.4 |
| d _a - min. | 147 mm |

| | |
|----------------------------------|----------|
| d_a - max. | 163 mm |
| Minimum Buy Quantity | N/A |
| d_b - min. | 184 mm |
| r_a - max. | 3 mm |
| $r_{1,2}$ min. | 4 mm |
| $r_{3,4}$ min. | 4 mm |
| D_a - max. | 261.4 mm |
| D_1 ? | 235.2 mm |
| d_1 ? | 181 mm |
| $r_{1,2}$ - min. | 4 mm |
| $r_{3,4}$ - min. | 4 mm |
| Basic dynamic load rating C | 1060 kN |
| Basic dynamic load rating - C | 1060 kN |
| Fatigue load limit P_u | 137 kN |
| Calculation factor k_r | 0.38 |
| Fatigue load limit - P_u | 137 kN |
| Calculation factor - k_r | 0.38 |
| Basic static load rating C_0 | 1250 kN |
| Basic static load rating - C_0 | 1250 kN |